



SPINDEX TECHNOLOGIES CO., LTD.

No. 21, Ln. 204, Zhongxing N. ST., Sanchong Dist.,
New Taipei City 241, Taiwan (R. O. C.)

TEL : +886-2-29950267

E-mail:spindex@ms34.hinet.net

FAX : +886-2-29958334

Web:<http://www.spindex.com.tw>

Technical Specifications for Built-In Motor-Spindle Spindle type : SY-62(CP-368)

1. Spindle housing diameter (mm) and mounting:	Ø61.91h6 vertical or horizontal
2. Maximum speed (rpm) :	60,000rpm - Grease
3. Nominal speed:	41,000 rpm
4. Motor type:	integrated induction motor
5. Motor power S1/S6 (Kw) :	1.0/1.2Kw
6. Motor voltage / poles :	210v/2
7. Spindle torque at power S1/S6(Nm):	0.22/0.27Nm
8. Shaft orientation Encoder (vector control):	N/A
9. Bearing type:	hybrid bearing
10. Front bearing inner diameter(mm):	Ø17mm
11. Bearing preloading :	constant springs preload
12. Bearing lubrication:	life time grease
13. Bearing temperature sensor :	N/A
14. Tool interface:	Collet type
15. Clamping capacity :	Ø3.175~6mm
16. Tool release :	pneumatic
17. Motor cooling :	water with additive
18. Spindle cooling (Kcal/h) :	1,000 Kcal/h
19. Coolant through shaft :	N/A
20. Converter nominal power(KVA) :	2.22 KVA
21. Spindle weight :	5.5Kgs



SPINDLEX TECHNOLOGIES CO., LTD.

No. 21, Ln. 204, Zhongxing N. ST., Sanchong Dist.,
New Taipei City 241, Taiwan (R. O. C.)

TEL : +886-2-29950267

E-mail:spindlex@ms34.hinet.net

FAX : +886-2-29958334

Web:<http://www.spindlex.com.tw>

Spindle type : SY-62(CP-368)

Power and Torque-diagram for Built-In Motor-Spindle

